Brisbane Yamaha

BRISBANE YAMAHA We Know Boats!

0

Phone: 07 3888 1727

Email: online@brisbaneyamaha.com.au Website: https://www.brisbaneyamaha.com.au

Boat Details

PriceOUR PRICE: \$6,745Boat BrandYamahaModelT25XWTCLength0.00

Year 2022 Category Boat Engines and Outboards

Hull Style Hull Type
Power Type Stock Number

Condition New State Queensland

Suburb BURPENGARY Engine Make

Description

T25XWTC Yamaha 4 Stroke 25hp Extra-Long Shaft HIGH THRUST, Electric Start, Power Trim & Tilt System, Multi-Functional Tiller Handle or Forward Control OUTBOARD FOR SALE

The new High Thrust T25 delivers the power and grip to manoeuvre heavier small vessels with exceptional efficiency. Based on the award winning F25, Yamaha developed the new T25 in response to requests for lightweight electronic fuel injected performance in a small, high-thrust configuration.

The new T25 benefits from the technology and features available on the standard F25 model, including an exceptional power to weight ratio, variable trolling rpm control and the ability to connect to Yamaha's Command Link Digital Gauges.

The new T25 is available in both 20-inch (L) and 25-inch (X) shaft length to suit a wider variety of hulls. The T25 also comes fitted with a dual thrust propeller, specifically tested and developed for this outboard. These big-diameter, low-pitch propellers offer exceptional thrust and efficiency for pushing big loads in both forward and reverse.

Available in:

- T25LWTC- High Thrust, Electric Start, Multi-Functional Tiller Handle or Power Tilt System(Forward Control), Transom height Long
- T25XWTC- High Thrust, Electric Start, Multi-Functional Tiller Handle or Power Tilt System(Forward Control), Transom height Extra-Long

General Features:

POWER/PERFORMANCE

- Enhanced Acceleration and Performance Under Load
- Single Overhead Camshaft
- Wide-Span Mounting System

RELIABILITY/DURABILITY

- CDI Microcomputer
- Wet Sump Lubrication
- Engine Warning System
- Mechanical Single Throttle Valve Intake System
- SST Drive, Prop, Shift Shafts
- SST Steering Tube
- Magnetic Drain Plug
- Sacrificial Anodes
- YDC-30 Aluminium Alloy
- Phase Five TM Paint System
- Electro-deposited Powerhead Paint Process

CONVENIENCE/CONTROL

- High-Output (16-Amp) Alternator
- 45-Degree Steering in both Directions
- Built-In Resting Pads and Carry Handles
- Variable Trolling RPM Switch (VTS®)
- Freshwater Flush
- Spin-on Oil Filter
- Offset Steering Friction Lever
- Auto Decompression Device
- Vibration Reduction Mounting System
- C.A.R.B. Ultra Low Emissions 3 Star Rating
- External Oil Drain Plug
- Dual Thrust Propeller

Specifications

ENGINE
Engine Type
Two-cylinder, In-line
Displacement
432 cc
Bore x Stroke
65 x 65.1 mm
Full Throttle RPM Range
5000 - 6000
Variable Trolling RPM Range
750-1050 rpm
750–1050 rpm
900 rpm
Horsepower Rating at Prop shaft
25 hp at 5500 rpm
Compression Ratio
9.3:1
Fuel Induction/Scavenging
SOHC, 2 valves per cylinder
Alternator Output
16 amp
Starting Method
E = Electric Start with Manual Backup
Ignition
CDI Microcomputer
Lubrication
Wet Sump
Degree of Trim
-3° through +16° (PTT)
Degree of Tilt
-3° through +63° (PTT)
Exhaust
Through Propeller

Cooling
Water, Thermostatic Control
DRIVE
Gear Shift
F-N-R (Forward-Neutral-Reverse)
Gear Ratio
2.08:1
SHAFT LENGTH
See Model Code
L = 20" X = 25"
FUEL AND LUBRICATION
Recommended Fuel
Regular Unleaded
Recommended Fuel Filtration
Yamaha 10-Micron or Mini-10TM
Recommended Oil
Yamalube® 4-M 10w-30
Engine Oil Capacity
1.1L / 1.0L (w/without filter)
LIMITED WARRANTY
Recreational
2 + 2 Years
Commercial
1 Year
WEIGHT
• T25LWTC = 64 kg • T25XWTC = 70 kg
*Weight estimated at time of publishing includes standard propeller, which is included with this model. Weight is measured without motor and gearcase oil.
Prices do not include fitting or accessories where applicable.
It is a Yamaha Australia stipulation that all Yamaha Outboards be fitted and personally delivered by the selling Yamaha outboard dealership.

Features

Engine Details

Horse Power

25